

# YL-65



## STANDARD DIE SETS

Size	Range (mm)	Length
<b>32-10</b>	10-13	55
<b>32-13</b>	13-16	55
<b>32-16</b>	16-19	55
<b>32-19</b>	19-22	55
<b>32-22</b>	22-26	55
<b>32-26</b>	26-30	55
<b>32-30</b>	30-34	75
<b>32-34</b>	34-39	75
<b>32-39</b>	39-45	75
<b>32-45</b>	45-52	90
<b>32-52</b>	52-57	90
<b>32-57</b>	57-64	90
<b>32-64</b>	64-69	100
<b>32-69</b>	69-74	100
<b>32-74</b>	74-78	110
<b>32-78</b>	78-88	110

## TECHNICAL SPECIFICATIONS

<b>Max hose size</b>	2" 4SP
<b>Crimping force (kN):</b>	2400
<b>Max crimping Ø (mm):</b>	88
<b>Max opening (mm):</b>	die diameter + 65
<b>Standard motor:</b>	5,5kW 380V 3-Ph
Different voltage versions available	
<b>Control</b>	Digital control
<b>Master dies opening / Length (mm):</b>	163/97
<b>Crimping range (mm):</b>	10 - 88
<b>Weight (kg)</b>	1200 (without oil)
<b>Dimensions (LxWxH mm)</b>	850 x 1000 x 1500
<b>Die sets</b>	Standard
10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78	
<b>Quick Change-set</b>	Standard
<b>Back stop device</b>	Standard
<b>Foot pedal</b>	Standard

**DHYDRO.COM**