

YL-80



STANDARD DIE SETS

| Size | Range (mm) | Length |
|---------------|------------|--------|
| 32-10 | 10-13 | 55 |
| 32-13 | 13-16 | 55 |
| 32-16 | 16-19 | 55 |
| 32-19 | 19-22 | 55 |
| 32-22 | 22-26 | 55 |
| 32-26 | 26-30 | 55 |
| 32-30 | 30-34 | 75 |
| 32-34 | 34-39 | 75 |
| 32-39 | 39-45 | 75 |
| 32-45 | 45-52 | 90 |
| 32-52 | 52-57 | 90 |
| 32-57 | 57-64 | 90 |
| 32-64 | 64-69 | 100 |
| 32-69 | 69-74 | 100 |
| 32-74 | 74-78 | 110 |
| 32-78 | 78-87 | 110 |
| 80-84 | 84-92 | 110 |
| 80-92 | 92-100 | 110 |
| 80-100 | 100-108 | 110 |
| 80-108 | 108-116 | 110 |
| 80-116 | 116-126 | 110 |

TECHNICAL SPECIFICATIONS

| | |
|---|--------------------|
| Max hose size | 4" |
| Crimping force (kN): | 3200 |
| Max crimping Ø (mm): | 126 |
| Max opening (mm): | die diameter + 80 |
| Standard motor: | 5,5kW 380V 3-Ph |
| Different voltage versions available | |
| Control | Digital control |
| Master dies opening / Length (mm): | 220/97 |
| Crimping range (mm): | 10 - 126 |
| Weight (kg) | 1350 (without oil) |

| | |
|------------------------------|---|
| Dimensions (LxWxH mm) | 850 x 1000 x 1600 |
| Die sets | Standard |
| | 10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78-84-92-100-108-116 |
| Quick Change-set | Standard |
| Back stop device | Standard |
| Foot pedal | Standard |

DHYDRO.COM